

# PRE-PROTECTION

## Stop Emerging Moisture



### Anti-Stain Coating 2015

Liquid, 2-component coating based on a polymer formulation, containing filling agents, free of solvents, excellently stable to alkali (especially to laying mortar), weather-resistant, thin layer applications allows high spreading rate, mixing ratio 2:1 by volume

#### Application:

For the lateral and rear sealing of natural and artificial stone slabs for a secure prevention of blooming and stains caused by moisture. Avoids or reduces formation of rust stains. The quartz sand dispersed on the Anti-Stain Coating 2015 layer acts as an adhesion primer to the laying mortar.

| Size                | Sales Unit | Art. No. |
|---------------------|------------|----------|
| <b>Colour: Grey</b> |            |          |
| 10 kg bucket        | 1          | 1 17 18  |
| 5 kg bucket         | 1          | 1 17 29  |
| 2 kg bucket         | 3          | 1 28 43  |
| 1 kg bucket         | 3          | 1 28 44  |



VIDEO



### Protector

Pre-impregnation based on silicone, contains solvents, low odour during application

#### Application:

Long lasting, water and dirt-repellent protective treatment to prevent/reduce damage resulting from rising damp (efflorescence) of wall and floor covering made of absorbent, mineral substances, e.g. natural and artificial stone. Subsequent treatment is possible with AKEMI impregnations and colour intensifiers. Also used as a grouting aid.

| Size                      | Sales Unit | Art. No. |
|---------------------------|------------|----------|
| <b>Colour: Colourless</b> |            |          |
| 1000 ml bottle            | 6          | 1 19 37  |
| 5000 ml metal canister    | 2          | 1 19 38  |

Coverage: approx. 5 -20 m<sup>2</sup>/liter;  
depending on the absorbency of the stone