

UC 3SFL
3.6V Charger

Features

- Large charge indicator lamp



Specifications		
Charging Voltage	3.6V	
Battery	Type	Cassette
	Assortment	Lithium-ion
Fan cooling	No	

UC 7SL
7.2V Charger

Li-ion

Features

- Large charge indicator lamp with 4 color LED status lights
- Battery capacity lamp (4 stages)
- Low-temperature charge (-10° C and above)



Specifications		
Charging Voltage	7.2V	
Battery	Type	Cassette
	Assortment	Lithium-ion
Fan cooling	No	

UC 12SL
10.8 - 12V Peak Charger

Li-ion

Features

- Compatible with engine generators
- Low-temperature charge (From -10°C)



Specifications		
Charging Voltage	10.8 - 12V Peak	
Battery	Type	Slide
	Assortment	Lithium-ion
Fan cooling	Yes	

UC 18YFSL
14.4V / 18V Charger

Li-ion

Features

- Rapid charging



Specifications		
Charging Voltage	14.4V and 18V	
Battery	Type	Slide
	Assortment	Lithium-ion
Fan cooling	Yes	

The actual charging time can vary depending on the surrounding temperature & battery condition

Cordless	Chargers/ Batteries	Drilling	Demolition	Fastening	Grinding	Polishing & Sanding	Sawing	Cutting	Planing & Routing	Miscellaneous Pneumatic	E - Tech Line	Accessories
----------	------------------------	----------	------------	-----------	----------	------------------------	--------	---------	----------------------	----------------------------	---------------	-------------

CORDLESS CHARGER

UC 18YSL3
14.4V / 18V Charger

Li-ion

Features

- Compatible with engine generators
Low-temperature charge (From -10°C)
- High visibility large charge indicator
lamp & full-color LED lights
- USB port (5V, 2A)



Specifications		
Charging Voltage	14.4 and 18V	
Battery	Type	Slide
	Assortment	Lithium-ion
Fan cooling	Yes	

The actual charging time can vary depending on the surrounding temperature & battery condition

CHARGE FASTER.
GO FURTHER.

FAST CHARGER UC36YSL2

Get back to work in no time with the newest HiKOKI Fast Charger. The UC36YSL2 delivers lightning-fast charging, thanks to its advanced cooling system and overcharging and overheating protection. Its bright charge status light makes it easy to check the battery anywhere on the worksite, always signaling that you're ready to start your next project. Go get yours!



* VS. UC18YSL3. When charging a BSL3640MVT/BSL36B18X/BSL36B18 battery.





SHAPING THE FUTURE OF CONSTRUCTION

BSL 1850MA
18V Lithium-ion
Slide Battery

Li-ion

Features

- Remaining battery indicator
- Compatible with all HiKOKI 18V rapid chargers



Specifications	
Voltage & Capacity	18V - 5.0Ah
Cooling System	Yes
Dimensions (L x H x W)	116 x 69 x 76mm
Weight	650g
Compatible Products	All existing 18V slide-type tools
Compatible Chargers	All chargers for 14.4V - 36V Lithium-ion slide batteries

BSL 1840M
18V Lithium-ion
Slide Battery

Li-ion

Features

- Remaining battery indicator
- Compatible with all HiKOKI 18V rapid chargers



Specifications	
Voltage & Capacity	18V - 4.0Ah
Cooling System	Yes
Dimensions (L x H x W)	134 x 83 x 54mm
Weight	600g
Compatible Products	All existing 18V slide-type tools
Compatible Chargers	All chargers for 14.4V - 36V Lithium-ion slide batteries

The actual charging time can vary depending on the surrounding temperature & battery condition

Cordless
Chargers/ Batteries
Drilling
Demolition
Fastening
Grinding
Polishing & Sanding
Sawing
Cutting
Planing & Routing
Miscellaneous Pneumatic
E - Tech Line
Accessories

CORDLESS BATTERIES

Cordless
Chargers/ Batteries
Drilling
Demolition
Fastening
Grinding
Polishing & Sanding
Sawing
Cutting
Planing & Routing
Miscellaneous Pneumatic
E - Tech Line
Accessories

BSL 1820M
18V Lithium-ion
Slide Battery

Li-ion

Features

- Remaining battery indicator
- Compatible with all HiKOKI 18V rapid chargers



Specifications	
Voltage & Capacity	18V - 2.0Ah
Cooling System	Yes
Dimensions (L x H x W)	116 x 76 x 49mm
Weight	380g
Compatible Products	All existing 18V slide-type tools
Compatible Chargers	All chargers for 14.4V - 36V slide-type Lithium-ion batteries

BSL 1240M
10.8 - 12V Peak Lithium-ion Slide Battery

12V PEAK
Li-ion



Specifications	
Voltage	10.8 - 12V Peak
Capacity	4.0Ah
Dimensions (L x H x W)	91 x 45 x 74mm
Charging Time	Approx. 60 min (when using the UC12SL)
Compatible Products	UC12SL

BSL 36A18
36V / 18V MULTI VOLT
Lithium-ion Slide Battery

MV
MULTI VOLT
Li-ion

Features

- 1,080W high power output
- Automatic voltage change between 36V 2.5Ah and 18V 5.0Ah depending on the tool's voltage
- Remaining battery indicator
- Full compatibility with the existing 18V slide range and 14.4V-36V slide battery chargers



Specifications	
Voltage & Capacity	36V - 2.5Ah / 18V - 5.0Ah
Cooling System	Yes
Dimensions (L x H x W)	116 x 69 x 76mm
Charging Time	Approx. 32 min (when using the UC18YSL3)
Compatible Products	All existing 18V slide-type tools MULTI VOLT 36V tools
Compatible Chargers	All chargers for 14.4V - 36V slide-type Lithium-ion batteries

The actual charging time can vary depending on the surrounding temperature & battery condition

Li-ion

**Reinventing Power &
Durability.**

