

Stainfree Grout



STELLAR™

STELLAR™ GROUT

It is a single component, high performance modified joint filling grout, which offers excellent colour uniformity, durability, stain protection, and beautiful grout joints in an easy-to-use, non-sag formula, with no hassle of mixing two packs or any other liquids like water or latex liquid.

Application

STELLAR™ Grout is best suited for internal & external tile joints grouting of residential / commercial installations where materials must resist physical abuse, shock & chemical attack. Excellent for external swimming pool & water bodies. It is NOT a waterproof material for joints or surfaces.

Advantages

- Single Component
- Suitable for joints of 1.5 mm to 12 mm
- Non-sag formula for floors and walls
- Designed for exterior use

Coverage: Varies with tile size and grout width

Packaging: 1/5th unit - 1 kg & 1 unit - 5 kg pails

Colour: Available in 5 colours



SP-100™

SP-100™ STAINFREE GROUT FOR FLOOR N' WALL

SP-100™ Stainfree Grout for Floor N' Wall is a stainfree, colour-fast, chemical resistant, 100% solid epoxy grout suitable for ceramic tiles, vitrified tiles, marble and stone, especially in stain prone areas such as kitchens and washrooms (residential and commercial installations).

Applications: Kitchens, bathrooms, swimming pools, fountains, water bodies, hospitals, operation theatres, sterilization rooms, restaurants, cafeterias, light industrial applications and high traffic areas. It is NOT a waterproof material for joints or surfaces.

Advantages:

- 100% stainfree
- Strong and durable
- Chemical and temperature resistant
- Anti bacterial and anti fungal

Coverage: Varies with tile size and grout width

Packaging: 1/5th unit - 1 kg & 1 unit - 5 kg pails

Factory proportioned unit consisting of three conveniently packed components - Hardener, Resin (Part A and Part B) and Coloured Filler Powder (Part C).

Colour: Available in a range of more than 36 colours

Compliance: Meets the following standards

- ANSI: A 118.3
- EN 13888: RG2
- VOC: Very low



SP-100™ DUO

SP-100™ DUO STAINFREE GROUT FOR FLOOR N' WALL

SP-100™ DUO Stainfree Grout for Floor N' Wall is a Stain Resistant, Water Resistant & Germ Resistant grout for Floor & Wall. SP-100™ DUO Tile-Joint is suitable for ceramic tiles, vitrified tiles, marble and stone, especially in stain prone areas such as kitchens and washrooms.

Applications:

Kitchens, bathrooms, swimming pools, fountains, water bodies, hospitals, operation theatres, sterilization rooms, restaurants, cafeterias, light industrial applications and high traffic areas. It is NOT a waterproof material for joints or surfaces.

Advantages:

- 100% stainfree
- Uniform colour
- Chemical and temperature resistant
- Non-cracking or powdering

Coverage: Varies with tile size and grout width.

Packaging: 1/5th unit - 1 kg & 1 unit - 5 kg pail

Colour: Available in a range of more than 10 colours

Compliance: Meets the following standards

- ANSI: A 118.3
- EN 13888: RG2
- VOC: Very low

Cementitious Grout



600

LATICRETE® 600 SERIES UNSANDED GROUT

A carefully prepared blend of portland cement, graded aggregates, polymer fortifiers and colour-fast pigments, it is designed for joint width 1mm to 3mm, for porous & absorbent type tiles, non-vitreous clay tiles, and marble & glazed wall tiles. Suitable for internal and external applications.

Applications: Residential, commercial, external facades

Advantages: • For tile joints 1 - 3mm • Uniform colour • Hard and durable • Economical

Mixing Ratio: Use approx. 400 ml of water or LATICRETE® 1776 Grout Admix Plus for 1 kg of LATICRETE® 600 Series Unsanded Grout.

Coverage: Varies with tile size and grout width

Packaging: 500g, 1 kg and 10 kg bags

Colour: Available in a range of more than 36 colours

Compliance: Meets the following standards

• ANSI: A 118.6 • EN 13888: CG1 • VOC: Very low



500

LATICRETE® 500 SERIES SANDED GROUT

LATICRETE® 500 Series Sanded Grout is made of polymer blended portland cement, graded aggregates, fortifiers and colour-fast pigments, it provides a tile joint that is strong, hard and durable. Designed for joint width of 3mm to 12mm for non-absorbent and vitreous tiles, it is suitable for interior and exterior use.

Applications: Residential, commercial, external facades

Advantages: • For tile joints 3-12mm • Uniform colour • Hard and durable • Economical

Mixing Ratio: Use approx. 2 ltr of LATICRETE® 1776 Grout Admix Plus for 10 kg of 500 Series Sanded Grout.

Coverage: Varies with tile size and grout width

Packaging: 10 kg bag

Colour: Available in a range of more than 36 colours

Compliance: Meets the following standards

• ANSI: A 118.6 • EN 13888: CG1 • VOC: Very low

Grout Admix



1776

LATICRETE® 1776 GROUT ADMIX PLUS

LATICRETE® 1776 Grout Admix Plus is specially designed Latex Admix to be used with Sanded & Unsanded Grout.

Applications: It improves the performance of portland cement grouts for all types of ceramic tile, brick, marble, natural stone and agglomerate stone installations.

Advantages: • Colour-fastness • Flexibility • Compressive strength • Shock and chemical resistance • Reduces water absorption • Easy to clean

Coverage: Varies by application.

Packaging: 200 ml, 400 ml, 5 ltr and 20 ltr. pails

Compliance: • VOC: Very low

Speciality Grout



Dazzle™

LATAPOXY® Dazzle™ Grout for Floor N' Wall

LATAPOXY® Dazzle™ Grout for Floor N' Wall is an epoxy grout specifically designed to enhance aesthetics and performance. It is suitable for use with ceramic tiles, vitrified tiles, glass mosaic tiles, designer tiles and natural stone.

Applications: • Restaurants • Hotels • Kitchens • Bathrooms • Lobbies
• Swimming Pools • Showrooms

Advantages: • Good aesthetic appeal • Stainfree • Strong & durable
• Chemical & temperature resistant

Coverage: Varies with tile size and grout width

Packaging: Net Weight: 1/4 unit (1.25 kg); 1 unit (5 kg) pails

Factory proportioned kit consisting of three conveniently packed components - Hardener, Resin (Part A and Part B) and Dazzle Coloured Filler Powder (Part C).

Colour: Available in 10 colours and 3 finishes - Gold, Silver and Copper

Compliance: Meets the following standards

- ANSI: A 118.3
- EN 13888: RG2
- VOC: Very low



2000

LATAPOXY® 2000 INDUSTRIAL EPOXY GROUT

Three part, 100% solid epoxy grout specifically formulated for maximum chemical and high temperature resistance. It is recommended for extreme industrial and commercial applications such as dairies, food processing units, commercial kitchens, breweries, beverage plants, pharmaceuticals, and meat packaging plants

Applications: Industrial food processing plants, beverage plants, battery plants and environments requiring high temperature and chemical resistance.

Advantages:

- Heavy duty industrial grout • Superior chemical & heat resistance
- Water cleanable & fast curing • Highly resistant to bacteria attack

Coverage: Varies with tile size and grout width

Packaging: #2 unit (10 kg) pail

Factory proportioned unit consisting of three conveniently packed components - Hardener, Resin (Part A and Part B) and Coloured Filler Powder (Part C)

Colour: Black and Grey

Compliance: Meets the following standards

- ANSI: A 118.3
- EN 13888: RG2
- VOC: Very low