

TILE & STONE ADHESIVE RANGE

Roff Masterfix

Highly flexible 2 component PU based thin set adhesive for fixing all kinds of tiles and stones including composites, engineered/ nano stone, metal and glass tiles on interior and exterior floor and wall.

FEATURES

- Suitable for fixing tiles/stones over diverse critical cement-based substrate, metal substrates, epoxy/ PU based substrate, drywall boards, Rubber, PVC, plywood, wood derivative etc.
- High bond strength, flexible & heat resistant
- Chemical resistant & resistance to solvents, alkalis & oils



PACKAGING UNITS	COLOUR	COVERAGE	SHELF LIFE
4 kg 8 kg	White	16 to 20 sq. ft./ 4 kg pack using 3 mm x 3 mm notch	24 months



Roff Yogafix

For fixing all types & sizes of vitrified tiles & natural stones in interior or exterior situations, especially those exposed higher deformations/ vibration like lift area, external cladding, metro stations etc.

FEATURES

- Highly flexible - > 5 mm deformation
- Very high initial grab
- High Open Time & adjustability
- High load bearing capacity.



PACKAGING UNITS	COLOUR	COVERAGE	SHELF LIFE
20 kg	Grey White	5 to 6 m²/ 20 kg bag at 3 mm bed thickness	12 months



Roff Extrofix Ultra

For fixing of fully vitrified tiles, large format tiles & natural stones in interior or exterior situations, especially those exposed permanently to external conditions or substrates subject to deformations or vibrations.

FEATURES

- A polymer enriched cementitious flexible tile adhesive
- Specially designed for external cladding
- Prolonged workability & non-slip
- High adhesive bond strength



PACKAGING UNITS	COLOUR	COVERAGE	SHELF LIFE
20 kg	Grey White	5 to 6 m²/ 20 kg bag at 3 mm bed thickness	12 months



For light and white coloured natural stones and glass mosaics tiles, use white variant.

TILE & STONE ADHESIVE RANGE

Roff Extrofix

For fixing all types of tiles, natural stones on external floors and walls exposed to external conditions subject to deformation/ vibrations.

FEATURES

- Extended open time
- High grab and non-sag
- Excellent bond strength
- Deformable/ Flexible

PACKAGING UNITS	COLOUR	COVERAGE	SHELF LIFE
20 kg	Grey White	5 to 6 m ² / 20 kg bag at 3 mm bed thickness	12 months



Roff Vitrofix Ultra

For fixing all sizes and types of tiles, natural stones and glass mosaics on internal floor, wall and external floor.

Recommended for all applications like window, door frame & swimming pool.

FEATURES

- Ready to use & needs only mixing with water
- Superior bond strength
- Superior grab
- Extended open time

PACKAGING UNITS	COLOUR	COVERAGE	SHELF LIFE
20 kg	Grey White	5 to 6 m ² / 20 kg bag at 3 mm bed thickness	12 months



Roff Vitrofix

For fixing any size vitrified tiles, natural stones and glass mosaics on internal floor & wall.

FEATURES

- Ready to use, needs only mixing with water
- Better workability
- High grab and non-sagging
- Excellent bond strength

PACKAGING UNITS	COLOUR	COVERAGE	SHELF LIFE
20 kg	Grey White	5 to 6 m ² / 20 kg bag at 3 mm bed thickness	12 months



For light and white coloured natural stones and glass mosaics tiles, use white variant.

TILE & STONE ADHESIVE RANGE

Roff Non-Skid Adhesive (NSA)

For fixing large size vitrified tiles & natural stones on floor & wall and tile-on-tile application for internal areas.

FEATURES

- Tile-on-tile application
- High bond strength
- Higher open time
- Easy mixing and application

PACKAGING UNITS	COLOUR	COVERAGE	SHELF LIFE
5 kg 20 kg 30 kg	Grey	5 to 6 m ² / 20 kg bag at 3 mm bed thickness	12 months
20 kg 50 kg	White	7.5 to 8 m ² / 30 kg bag at 3 mm bed thickness	



Roff New Construction Tile Adhesive (NCA)

Ideal for fixing high porosity tiles like ceramic tiles, terracotta and quarry tiles of regular size on both floor & wall for indoor application & small/regular size vitrified tiles on interior floor.

FEATURES

- Ready to use, needs no curing
- Saves time & increases productivity
- Excellent adhesion & low shrinkage
- Sag-resistant

PACKAGING UNITS	COLOUR	COVERAGE	SHELF LIFE
20 kg 30 kg	Grey	5 to 6 m ² / 20 kg bag at 3 mm bed thickness 7.5 to 8 m ² / 30 kg bag at 3 mm bed thickness	12 months



Roff Tile Bonder

A polymer additive which needs to be pre-mixed with cement/ cement & sand and then should be mixed with water for installing tiles and natural stones using the traditional cement slurry over freshly laid levelling bed/ machan.

FEATURES

- Easy to use & no special tools required
- Greatly increases pot life, open time & adjustability
- Improves adhesion & bond strength
- Economical solution for tile fixing

PACKAGING UNITS	COLOUR	COVERAGE	SHELF LIFE
300 g	White Powder	1 pouch of 300 g Roff Tile Bonder in 1 cement bag of 50 kg	12 months



For light and white coloured natural stones and glass mosaics tiles, use white variant.



Scan to know
more about
adhesive coverage



Scan to know
more about
adhesive selector

TILE & STONE ADHESIVE RANGE

Fevi Kwik 102

Low viscosity, fast-setting cyanoacrylate adhesive designed for tile, marble, and granite fixing. Regular strength makes it ideal for temporary applications, allowing for easy removal of tiles.

FEATURES

- Extra fast-setting (Sets within 5 secs)
- Regular strength
- Clear finish

PACKAGING UNITS

20 g 50 g

COLOUR

Clear
transparent

COVERAGE

As per requirement



Fevi Kwik 203

Low viscosity, medium-setting, high-strength cyanoacrylate adhesive with a clear finish. Ideal for permanent fixing of tiles, marble, and granite. Its low blooming nature ensures a clear finish in signage applications. It is a multi-substrate multi-application product

FEATURES

- Extra strength
- No blooming /Extra clear

PACKAGING UNITS

20 g 50 g

COLOUR

Clear
transparent

COVERAGE

As per requirement



GROUT RANGE

Roff Starlike

Two component epoxy grout with patented quartz technology, applicable for interior and exterior environment due to its UV resistant tech, its chemical & stain resistant technology makes it best suited for residential and industrial spaces.

FEATURES

- Easy to mix & clean
- Stain & UV resistant
- Acid & chemical resistant
- Fills joints upto 1-15 mm
- More coverage



PACKAGING UNITS	COLOUR	COVERAGE	SHELF LIFE
1 kg 5 kg	24 Shades	Depends upon joint size	24 months

COVERAGE CHART*

Starlike Tile Grout Coverage in sq. ft./ kg													
Tile Dimension (mm)			Joint/ Grouting Width (mm)										
Length	Width	Thickness	2	3	4	5	6	8	10	12	13	14	15
450	300	6	110.7	73.8	55.3	44.3	36.9	27.7	22.1	18.4	17.0	15.8	14.8
600	300	6	123.0	82.0	61.5	49.2	41.0	30.7	24.6	20.5	18.9	17.6	16.4
600	600	8	138.3	92.2	69.2	55.3	46.1	34.6	27.7	23.1	21.3	19.8	18.4
800	800	8	184.5	123.0	92.2	73.8	61.5	46.1	36.9	30.7	28.4	26.4	24.6
1000	1000	10	184.5	123.0	92.2	73.8	61.5	46.1	36.9	30.7	28.4	26.4	24.6
1200	600	10	147.6	98.4	73.8	59.0	49.2	36.9	29.5	24.6	22.7	21.1	19.7
1200	800	10	177.1	118.1	88.5	70.8	59.0	44.3	35.4	29.5	27.2	25.3	23.6
1200	1200	12	184.5	123.0	92.2	73.8	61.5	46.1	36.9	30.7	28.4	26.4	24.6
1600	800	12	164.0	109.3	82.0	65.6	54.7	41.0	32.8	27.3	25.2	23.4	21.9
1800	1200	12	221.3	147.6	110.7	88.5	73.8	55.3	44.3	36.9	34.1	31.6	29.5

Note :

(1) This is theoretical coverage. (2) For sq. mtr./ kg coverage, divide mentioned coverage by 10.764.

*Know the material needed for your site.

Roff Starlike Crystal

Two-component acid-resistant translucent epoxy grout for grouting clear and artistic vitreous mosaics. Applicable for interiors and exteriors.

FEATURES

- Translucent
- Stain resistant
- UV resistant
- Chemical resistant



PACKAGING UNITS	COLOUR	COVERAGE	SHELF LIFE
1 kg 5 kg	-	Depends upon joint size	24 months

GROUT RANGE

Roff Starlike Finishes

This component has to be added to neutral shades to obtain metallic effects to enhance the look of tiles.

FEATURES

- Metallic shining effect
- UV & Stain resistant

PACKAGING UNITS	COLOUR	COVERAGE	SHELF LIFE
100g	Gold, Silver, Copper	Depends upon joint size	24 months



Roff Rainbow Tile Mate Epoxy

Resin based 3 component Epoxy joint filler. For filling tile joints of high traffic areas such as hospitals, factory floors & kitchen.

FEATURES

- Easy maintenance & smooth texture
- Provides excellent chemical resistant property
- Non-cracking & non-powdering
- High degree of resistance to abrasion and impact

PACKAGING UNITS	COLOUR	COVERAGE	SHELF LIFE
For 1 kg pack : 184 g Base + 78 g Hardener & 738 g Filler For 5 kg pack : 920 g Base + 390 g Hardener & 3690 g Filler	27 Shades	Depends upon joint size. Refer to the coverage chart.	24 months



COVERAGE CHART*

RTM Epoxy Tile Grout Coverage in sq. ft./ kg										
Tile Dimension (mm)			Joint/ Grouting Width (mm)							
Length	Width	Thickness	2	3	4	5	6	8	10	12
450	300	6	92.2	61.5	46.1	36.9	30.7	23.1	18.4	15.4
600	300	6	102.5	68.3	51.2	41.0	34.2	25.6	20.5	17.1
600	600	8	115.3	76.9	57.6	46.1	38.4	28.8	23.1	19.2
800	800	8	153.7	102.5	76.9	61.5	51.2	38.4	30.7	25.6
1000	1000	10	153.7	102.5	76.9	61.5	51.2	38.4	30.7	25.6
1200	600	10	123.0	82.0	61.5	49.2	41.0	30.7	24.6	20.5
1200	800	10	147.6	98.4	73.8	59.0	49.2	36.9	29.5	24.6
1200	1200	12	153.7	102.5	76.9	61.5	51.2	38.4	30.7	25.6
1600	800	12	136.6	91.1	68.3	54.7	45.5	34.2	27.3	22.8
1800	1200	12	184.5	123.0	92.2	73.8	61.5	46.1	36.9	30.7

Note :

(1) This is theoretical coverage. (2) For sq. mtr./ kg coverage, divide mentioned coverage by 10.764.

*Know the material needed for your site.

GROUT RANGE

Roff Sparkles

It is to be mixed with epoxy grout (Base + Hardener + Filler) to get special effect and enhance the beauty of the product. Specially designed filler mainly used to create particular special effects in epoxy tile grout.

FEATURES

- Easy to mix, apply & clean
- Enhance aesthetic look of tiles
- Stain free & easily cleanable with water (under fresh condition)

T28



PACKAGING UNITS	COLOUR	COVERAGE	SHELF LIFE
100g	Gold, Silver, Copper	3 - 7% of Roff RTM Epoxy (Base + Hardener + Filler)	24 months

Roff Rainbow Tile Mate

A water-resistant cementitious tile joint filler. For filling tile joints on floor & wall tiles. Fills joints upto 5 mm.

FEATURES

- High compressive, tensile & flexural strength
- Water-resistant property
- Easy to use and clean
- Firmly holds tiles together to give them longevity

Note: Unitint & Piditint can be used with these shades.

T11



PACKAGING UNITS	COLOUR	COVERAGE	SHELF LIFE
500g 1 kg 10 kg	18 Shades	Depends upon joint size	12 months

Roff Rainbow Tile Mate Additive

Additive for cementitious tile grout.

A liquid additive to be used with cementitious colour tile grouts to fill the tile joints of ceramic, vitrified tiles. RTM Wide Additive is used in place of water to improve the performance of RTM w.r.f. colour fastness, flexibility, waterproof & abrasion resistance.

FEATURES

- Improves water resistance
- Flexible joint filling

T14



PACKAGING UNITS	COLOUR	COVERAGE	SHELF LIFE
200 ml 1 Ltr	-	Depends upon joint size	12 months



Scan to know more about tile joint visualizer

TILE CLEANER

Roff Cera Clean

Cleaning of all types of floor and wall tiles
It is a high quality tile maintenance cleaner*.

*Whitish spot/ layer as normally observed in the bathroom under plastic/ metal buckets can be removed with ease.

FEATURES

- Vitrified & ceramic tile cleaner
- Removes dirt & tough stains
- Safe on tiles



PACKAGING UNITS	COLOUR	COVERAGE	SHELF LIFE
500 ml 1 Ltr 5 Ltr	Red	-	12 months

UNDER TILE WATERPROOFING RANGE

Roff Hyguard EX

Polymer modified cementitious flexible waterproof coating for basements, roof slabs, water retaining structures, sunken slabs, terrace slabs, water tanks, bathrooms, damp walls, foundations, etc. Bridges hairline cracks in concrete.

FEATURES

- Excellent adhesion, bonds to porous and non-porous surfaces
- Protects concrete against water penetration, chlorides and carbonation
- Can bridge hairline cracks
- Non-toxic & hence recommended for water tanks



PACKAGING UNITS	COLOUR	COVERAGE	SHELF LIFE
9 kg	-	0.45-0.55 m ² / kg for 2 coats for total minimum thickness of 1 - 1.5 mm (DFT) approx. Depending upon the surface, the coverage will vary. To be protected by screed for best performance.	12 months

UNDER TILE WATERPROOFING RANGE

Roff Bond Repair

It is used as a bonding agent between old & new concrete, for cementitious substrates, waterproof coating to small areas in bathrooms, balconies & small roofs. It is also effective to make repair mortars & concrete in building rehab works.

SBR based bonding agent (Styrene Butadiene Rubber).

FEATURES

- Excellent adhesion to reinforcement & concrete
- Increases flexural strength & tensile strength of concrete & mortar
- Reduces shrinkage & water permeability in concrete & mortar
- Good as a bonding agent in repairs & renovations



W01

PACKAGING UNITS	COLOUR	COVERAGE	SHELF LIFE
500 ml 1 Ltr 5 Ltr	White	As a passivator coat - 1 : 1 (RBR : Cement) Coverage : 2-3 Rmtr/ ltr for 25 mm dia bar at 1 mm thickness	18 months
20 Ltr		As a waterproof coating - 1 : 1.5 (RBR : Cement) Coverage : 1.5-2 m ² / ltr for 2 coats at 300 micron thickness As bonding coat - 1 : 1 (RBR : Cement) Coverage : 2-3 m ² / ltr	

Roff Supercrete

It is a bonding agent for concrete repair and can be used as a patching mortar.

Acrylic polymer modifier for cementitious composites.

FEATURES

- Superlative bonding properties
- Can be used as a waterproof coating
- Static cracks can be filled with mortar made with Roff Supercrete
- Durable to UV exposure



R01

PACKAGING UNITS	COLOUR	COVERAGE	SHELF LIFE
1 Ltr 5 Ltr 20 Ltr	White	As a waterproof coating - 1 : 2 (Supercrete : Cement) Coverage : 1.5-2 m ² / ltr. for 2 coats at 1 mm thickness Coverage would depend upon porosity of substrate	12 months